

InfiniSolar E 5.5kw



- Pure sine wave output
- Self-consumption and Feed-in to the grid
- Programmable supply priority for PV, Battery or Grid
- User-adjustable battery charging current suits different types of batteries
- Programmable multiple operation modes: grid-tie, off-grid and grid-tie with backup
- Built-in timer for various mode of on/off operation
- Built-in 2 strings of MPP trackers
- Built-in 60A AC/Solar charger
- Optional DC switch

InfiniSolar E 5.5kw On-Grid Inverter with Energy Storage Specification

MODEL	InfiniSolar E 5.5kw
MAXIMUM PV INPUT POWER	6500W
RATED OUTPUT POWER	5500W
MAXIMUM CHARGING POWER	2880 W
GRID-TIE OPERATION	
PV INPUT (DC)	
Nominal DC Voltage / Maximum DC Voltage	360 VDC / 500 VDC
Start-up Voltage / Initial Feeding Voltage	116 VDC / 150 VDC
MPP Voltage Range	120 VDC ~ 450 VDC
Number of MPP Trackers / Maximum Input Current	2 / 2 x 13 A
GRID OUTPUT (AC)	
Nominal Output Voltage	202/208/220/230/240 VAC
Output Voltage Range	184 - 264.5 VAC*
Max. Output Current	23.9A*
Power Factor	> 0.99
EFFICIENCY	
Maximum Conversion Efficiency (DC/AC)	96%
European Efficiency@ Vnominal	95%
OFF-GRID OPERATION	
AC INPUT	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC
Acceptable Input Voltage Range	170 -280 VAC
Maximum AC Input Current	40 A
PV INPUT (DC)	
Maximum DC Voltage	500 VDC
MPP Voltage Range	120 VDC ~ 450 VDC
Number of MPP Trackers / Maximum Input Current	2 / 2 x 13 A
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	202/208/220/230/240 VAC
Output Waveform	Pure sinewave
Efficiency (DC to AC)	93%
HYBRID OPERATION	
PV INPUT (DC)	
Nominal DC Voltage / Maximum DC Voltage	360 VDC / 500 VDC
Start-up Voltage / Initial Feeding Voltage	116 VDC / 150 VDC
MPP Voltage Range	120 VDC ~ 450 VDC
Number of MPP Trackers / Maximum Input Current	2 / 2 x 13 A
GRID INPUT	
Nominal Output Voltage	202/208/220/230/240 VAC
Output Voltage Range	184 - 264.5 VAC*
Max. Output Current	23.9A*
AC INPUT	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC
Acceptable Input Voltage Range	170 -280 VAC
Maximum AC Input Current	40A
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	202/208/220/230/240 VAC
Efficiency (DC to AC)	93%
BATTERY & CHARGER	
Nominal DC Voltage	48 VDC
Maximum Solar Charge Current	60 A
GENERAL	
PHYSICAL	
Dimension, D x W x H (mm)	110 x 450 x 445
Net Weight (kgs)	16
INTERFACE	
External Safety Box (Optional)	RS-232/USB
Communication ports	Optional SNMP, Modbus and AS-400 cards
ENVIRONMENT	
Humidity	0 ~ 90% RH (Non-condensing)
Operating Temperature	0 to 40°C
Altitude	0 ~ 1000 m**

Product specifications are subject to change without further notice.



VDE-AR-N 4105
VDE 0126-1-1

AS4777 , AS/NZS3100, NRS-097-2-1
G83/2, G59



Voltronic Power

Advancing Power