

HYBRID INVERTER

HYD 3000-ES / HYD 4000-ES / HYD 5000-ES / HYD 6000-ES



Datasheet

HYD 3000-ES HYD 4000-ES HYD 5000-ES HYD 6000-ES

Battery Parameters				
Battery Type	Lithium-ion,Lead-acid			
Nominal battery Voltage	48V			
Battery voltage range	42-58V			
Battery Capacity	50-2000AH			
Maximum Charging /Discharging Power	3000W			
Maximum Charging Current	60A (programmable)			
Maximum Discharging Current	60A (programmable)			
Charging curve(Lithium-ion)	BMS			
Charging curve(Lead-acid)	3-stage adaptive with maintenance			
Depth of discharge	Lithium-ion:0-90% DOD adjustable Lead-acid:0-50% DOD adjustable			
Input DC(PV side)				
The max input power	3500W	4400W	5500W	6600W
Max DC power for single MPPT	2000W(160V-520V)	2600W(200V-520V)	3000W(250V-520V)	3500W(300V-520V)
The max DC input voltage	600V			
Start-up DC voltage	120V			
Nominal DC Voltage	360V			
MPPT operating voltage range	90-580V			
Full load DC voltage range	160V-520V	200V-520V	250V-520V	300V-520V
MPPT number	2			
The max DC input current	11A/11A			
The max DC input short current	13.2A/13.2A			
Output AC(Grid side)				
Rated Power	3000W	4000W	5000W	6000W
Max.Output Power	3000VA	4000VA	5000VA	6000VA
Nominal Grid Voltage	L/N/PE,220,230,240			
Operation phase	Single(L-N-PE)			
Max.Input/Output current	13.7A	18.2A	22.8A	27.3A
AC voltage Range	180V~276V(According to local standard)			
Grid Frequency range	44-55Hz/54-66Hz(According to local standard)			
THD	< 3%			
Power factor	1 default (+/-0.8 adjustable)			
Output AC(Emergency Power Supply)				
EPS rated power	3000VA			
Operation phase	Single(L-N-PE)			
EPS rated voltage, Frequency	230V,50/60Hz			
EPS rated current	13A			
Peak Output Apparent Power	4000VA , 10s			
THD	< 3%			
Switch time	5S default (1-60S adjustable)			
Efficiency				
MPPT efficiency	99.9%			
Max efficiency of solar Inverter	97.6%	97.6%	97.8%	98.0%
European efficiency of solar Inverter	97.2%	97.2%	97.3%	97.5%
MAX.Charging efficiency of battery	94.6%			
MAX.DisCharging efficiency of battery	94.6%			
Protection				
PV reverse polarity protection	Yes			
PV insulation detection	Yes			
Ground fault monitoring	Yes			
Over current protection	Yes			
Over voltage protection	Yes			
Battery soft start protection	Yes			
General Data				
Ambient temperature range	-30°C...+60°C(Above 45°C Derating)			
Standby Losses	< 5W			
Topology	High frequency insulation(for bat)			
DC-Switch	Optional			
Degree Of Protection	IP65			
Allowable Relative Humidity Range	0-100%, No Condensing			
Certification	NB/T32004-2013,AS4777,IEC62116,VDE0126-1G83/2,G59/3,EN50438,VDE-AR-N4105			
Communication	RS485,Wi-Fi/GPRS,SD,CAN2.0			
Protective class	Class I			
Max.Operating Altitude	2000m			
Current Sensor Connection	External			
Noise	< 25dB			
Weight	16KG			17KG
Cooling	Natural			
Dimension (W*H*D)	532*360*173			
Display	LCD display			
Warranty	5 Years or more			



High-yield

- Real time precise MPPT algorithm for max power generation
- Wide input voltage operation range
- Independent dual MPPT tracking, flexible solar roof system design

Reliable and Safe

- High efficiency low energy loss, Low maintenance
- High frequency isolation between battery & PV/grid
- Advanced battery management technology to protect the battery life.

Easier Operation

- Free site selection due to IP65
- 4' LCD clear, easy-to-read display
- Easy monitoring on phone (APP) & PC (web)

Multiple working modes

- PV & storage all in one, increases self consumption to 80%+, decreases reliance on the electrical grid, decreases the electricity bill.
- Stand alone mode (like UPS) available, ensures safe operation of critical loads
- Multiple operation modes selection: auto mode, time-of-use mode, timing mode, passive mode etc.

Intelligent grid management

- Reactive power capability
- Limits AC output when grid frequency is too high or too low
- Limits AC output when grid voltage is too high
- Built in zero export function (optional)

