


Single Phase
AC Coupled

X1-AC

High Voltage



**Simple.
Reliable.
Efficient**



High
Efficiency



Battery
Solution



IP65
Rated



Remote
Monitoring

3kW

3.6kW

4.6kW

5kW

X1-AC-3.0 / X1-AC-3.6 / X1-AC-4.6 / X1-AC-5.0

(Being developed)

(Being developed)

Features:

- Natural Cooling, quiet and low maintenance
- Max Efficiency up to 97%
- Multiple protection: RCD, isolation, over voltage
over temperature, earth protection, short-circuit protection, etc
- Compatible with High-voltage batteries
- Transformerless design with software and hardware protection.





X1-AC (SINGLE PHASE)

X1-AC-3.0

X1-AC-3.6

X1-AC-4.6
(Being developed)

X1-AC-5.0
(Being developed)

OUTPUT (AC)

Nominal AC power [VA]	3000	3680	4600	4999
Max. apparent AC power [VA]	3000	3680	4600	4999
Nominal grid voltage(AC voltage range) [V]	220/230/240 (180 - 280)			230/240 (180 - 280)
Nominal grid frequency/range [Hz]	50/60			50/60
Nominal AC current [A]	13	16	20	21.7
Max. AC current [A]	13.6	16.8 (16 for G83)	21	21.7
Displacement power factor	0.8 leading to 0.8 lagging			
THDi, rated power [%]	<2			

INPUT AC

Max. apparent AC power[VA]	3000	3680	4600	4999
Max. AC current[A]	13.6	16.8 (16 for G83)	21	21.7
Nominal grid voltage(AC voltage range)[V]	220/230/240 (180 - 280)			
Nominal grid Frequency/range[Hz]	50/60			

OUTPUT DC (BATTERY)

Battery voltage range [V]	70-400
Recommended battery voltage[V]	300
Max.continuous charge/discharge current [A]	35
Communication interfaces	CAN
Reverse connect protection	Yes

EFFICIENCY

MPPT efficiency	97.0
Max. Battery charge efficiency (GRID to BAT)	97.0
Max. Battery discharge efficiency (BAT to AC)	97.5

SAFETY & PROTECTION

Over/under voltage protection	Yes
DC isolation protection	Yes
Grid protection	Yes
DC injection monitoring	Yes
Residual current detection	Yes
Anti-islanding protection	Yes
Over load protection	Yes
Over heat protection	Yes

POWER CONSUMPTION

Standby consumption (Night) [W]	<10
---------------------------------	-----

STANDARD

Safety	IEC62477
EMC	EN 61000-6-1 / EN 61000-6-2 / EN 61000-6-3 / EN 61000-6-4
Certification	G98/G99/G100

ENVIRONMENT LIMIT

Degree of protection(according to IEC60529)	IP 65
Operating temperature range [°C]	-25~+60 (derating at 45)
Max. operation altitude [m]	2000
Humidity [%]	0~100, condensing
Storage temperature [°C]	-25~+60
Typical noise emission [dB]	<25

DIMENSION AND WEIGHT

Dimensions(WxHxD) [mm]	430*341.5*143			
Weight [kg]	15.5	15.5	16.3	16.3
Cooling concept	Natural			
Topology	Non-isolated			
Communication interfaces	Meter/Pocket WiFi(optional)/Pocket LAN(optional)/Pocket GPRS(optional)/RS485/DRM/USB/CT			
LCD display	Yes			
Standard warranty [year]	5-10			