

### Characteristics of a PV module

Manufacturer, model : **Trina Solar, TSM-510DE18M(II)**

Availability : Prod. Since 2020

Data source : UL 2020

<b>STC power (manufacturer)</b>	<b>Pnom</b>	<b>510 Wp</b>	<b>Technology</b>	<b>Si-mono</b>
Module size (W x L)	1.102 x 2.187	m <sup>2</sup>	Rough module area	Amodule 2.41 m <sup>2</sup>
Number of cells	2 x 75		Sensitive area (cells)	Acells 2.21 m <sup>2</sup>

**Specifications for the model (manufacturer or measurement data)**

Reference temperature	TRef	25 °C	Reference irradiance	GRef	1000 W/m <sup>2</sup>
Open circuit voltage	Voc	52.1 V	Short-circuit current	Isc	12.42 A
Max. power point voltage	Vmpp	43.2 V	Max. power point current	Impp	11.81 A
=> maximum power	Pmpp	510.2 W	Isc temperature coefficient	mulsc	6.2 mA/°C

**One-diode model parameters**

Shunt resistance	Rshunt	300 ohm	Diode saturation current	IoRef	0.012 nA
Serie resistance	Rserie	0.23 ohm	Voc temp. coefficient	MuVoc	-159 mV/°C
Specified Pmax temper. coeff.	muPMaxR	-0.36 %/°C	Diode quality factor	Gamma	0.98
			Diode factor temper. coeff.	muGamma	-0.001 1/°C

**Reverse Bias Parameters, for use in behaviour of PV arrays under partial shadings or mismatch**

Reverse characteristics (dark)	BRev	3.20 mA/V <sup>2</sup>	(quadratic factor (per cell))	
Number of by-pass diodes per module		3	Direct voltage of by-pass diodes	-0.7 V

**Model results for standard conditions (STC: T=25° C, G=1000 W/m<sup>2</sup>, AM=1.5)**

Max. power point voltage	Vmpp	43.4 V	Max. power point current	Impp	11.76 A
Maximum power	Pmpp	510.4 Wc	Power temper. coefficient	muPmpp	-0.35 %/°C
Efficiency(/ Module area)	Eff_mod	21.2 %	Fill factor	FF	0.789
Efficiency(/ Cells area)	Eff_cells	23.1 %			

